

**SUBMITTAL DATA SHEET**



AHU Heat Pump System	
Location: _____ Engineer: _____ Submitted to: _____ Submitted by: _____ Reference: _____	Approval: _____ Date: _____ Construction: _____ Unit #: _____ Drawing #: _____

<b>Set Code</b>	22023110000928
Indoor unit code	22023111000271
Outdoor unit code	22023116000162
<b>Set Model</b>	VCD18SA-1
Indoor unit model	B-VCD18SA-1
Outdoor unit model	A-VCD18SA-1
<b>Certified</b>	AHRI UL



SYSTEM PERFORMANCE DATA		
<b>Power supply</b>		
Normal Operational Voltage	(V, Ph, Hz)	208/230V,1Ph, 60Hz
Voltage Range	(V)	187-253
<b>Electrical</b>		
Minimum circuit ampacity(Outdoor)	(A)	16.0
Max.fuse(Outdoor)	(A)	20.0
Connection wiring		14AWG*2 Stranded, shielded
<b>Cooling</b>		
Capacity	(Btu/h)	18000(6880-21000)
Power Input	(W)	1450(260-1890)
Current	(A)	6.4(1.5-8.3)
SEER2	(Btu/W)	18.0
EER2	(Btu/W)	12.4
<b>Heating</b>		
Capacity	(Btu/h)	19000(2800-21000)
Power Input	(W)	1530(430-1920)
Current	(A)	6.8(2.5-8.5)
HSPF2-4	(Btu/W)	9.3
HSPF2-5	(Btu/W)	7.6
COP	W/W	3.64
Heat at 17F(H32)	(Btu/h)	13500
Heat at 5F(H42)	(Btu/h)	16500
COP at 5F(H42)	W/W	2.04

INDOOR UNIT DATA		
<b>Indoor fan motor</b>		
Model		ZKFD-250-8-1
Qty		1
Input	(W)	/
Output	(W)	/
RLA	(A)	2.0
Minimum circuit ampacity(Indoor)	(A)	2.5
Max.fuse(Indoor)	(A)	15
Speed(Hi/Mi/Lo)	(r/min)	/
<b>Air flow &amp; Noise level</b>		
Indoor air flow (Hi/Med/Lo) (No duct)	(CFM)	617.65/576.47/529.41/488.24
Indoor noise level (Hi/Med/Lo)	[dB(A)]	34/31/30
<b>Dehumidification</b>		
	(L/H)	1.67
<b>Indoor unit</b>		
Dimension (WxDxH)	(inch)	21.02x17.52x45.00
	(mm)	534x445x1143
Packing(WxDxH)	(inch)	26.57x20.87x48.62
	(mm)	675x530x1235
Net/Gross weight	(lbs.)	105.82/129.41
	(kg)	48/58.7
<b>Accessories</b>		
Adaptor for welding(3/4")	Qty	1
Adaptor for welding(3/8")	Qty	1


REFRIGERANT PIPE DATA		
Throttle type	Indoor unit	EEV for cooling
	Outdoor unit	EEV for heating
Design pressure	(PSIG)	550/340
Refrigerant Type		R410A
Refrigerant charge	oz	81.13
Refrigerant precharge	(ft)	25.0
	(m)	7.5
Additional charge for each ft	(oz/ft)	0.69
Additional charge for each m	(g/m)	65.0
Liquid side/ Gas side(indoor)	(inch)	3/8" / 3/4"
	(mm)	9.52/19
Liquid side/ Gas side(outdoor)	(inch)	3/8" / 5/8"
	(mm)	9.52/16
Max. pipe length	(ft)	98.4
	(m)	30.0
Max. difference in level	(ft)	65.6
	(m)	20.0
Connection method		Flared
Indoor(cooling)	(Deg. °F)	60~90
	(Deg. °C)	16~32
Indoor(heating)	(Deg. °F)	32~86
	(Deg. °C)	0~30
Outdoor(cooling)	(Deg. °F)	5~122
	(Deg. °C)	-15~50
Outdoor(heating)	(Deg. °F)	-22~75
	(Deg. °C)	-30~24

OUTDOOR UNIT DATA		
<b>Compressor</b>		
Type		Twin-ROTARY
Model		KTM240D57UMT
Brand		GMCC
Capacity	(Btu/h)	26409
Input	(W)	2085
Rated current (RLA)	(A)	10
Refrigerant oil/oil charge	(ml)	ESTER OIL VG74 670
<b>Outdoor fan motor</b>		
Model		ZKFN-80-8-3
Qty		1
Input	(W)	/
Output	(W)	80
RLA	(A)	1.0
Speed	(r/min)	800/700/580
<b>Air flow &amp; Noise level</b>		
Outdoor air flow (Max.)	(CFM)	1279
Outdoor noise level	[dB(A)]	57.0
<b>Outdoor unit</b>		
Dimension (WxDxH)	(inch)	35.04x13.46x26.50
	(mm)	890x342x673
Packing (WxDxH)	(inch)	39.17x15.67x29.13
	(mm)	995x398x740
Net/ Gross weight	(lbs.)	102.95/109.79
	(kg)	46.7/49.8
<b>Accessories</b>		
Adaptor for welding(3/4")	Qty	1
Adaptor for welding(3/8")	Qty	1
Adaptor (5/8" to 3/4")	Qty	1

**\*\*Verify Rating Plate Information  
Prior to Installation.**

Minimum Circuit Ampacity and Maximum Fuse Values  
May Have Changed from Original Specifications.

Indoor unit dimension



Model	Unit	Dimensions(mm)						Drain hole	
		A	B	C	D	E	F	L1	L2
18k~24k	mm	1143	534	445	400	260	585	Main drain	Overflow drain
	inch	45	21	17-1/2	15-3/4	10-1/4	23		
30k-48k	mm	1245	534	534	490	260	585		
	inch	49	21	21	19-5/16	10-1/4	23		
60k	mm	1346	534	622	580	260	585		
	inch	53	21	24-1/2	22-7/8	10-1/4	23		

Outdoor unit dimension

